

# PIC Wire & Cable

A Division of the Angelus Corporation

Ph 262-246-0500

Fax 262-246-0450

PO Box 330 Sussex, WI 53089

## Connector Specification

**P/N 1901008**

Approved


Date : 04/15/10

Rev. 3 (06/11/13)

Distribution : USER

Uncontrolled Document

### TNC Straight Plug w/Safety Wire Holes for S25070 Coaxial Cable



#### PERFORMANCE

Nominal Impedance 50 Ohms

Frequency Range 0 - 12 GHz

#### CONNECTOR WEIGHT (Each)

tbd

#### RoHS COMPLIANT

Complies to RoHS Standards

#### INSTALLATION

##### **Crimp Tooling:**

Center Contact : Solder

Crimp Ferrule : M22520 / 5 - 01 Tool  
M22520 / 5 - 27 Die Set  
(0.532 hex)

#### CONSTRUCTION

##### **Materials:**

Body	Brass, ASTM-B16, Alloy UNS 36000, H02
Coupling Nut	Brass, ASTM-B16, Alloy UNS 36000, H02
Center Contact	Brass, ASTM-B16, Alloy UNS 36000, H02
Dielectric	TFE Fluorocarbon, ASTM-D1710, Type 1, Grade 1
Ferrule	DHP Copper Alloy 122
Gasket	Silicone Rubber, ZZ-R-765
Shrink Sleeve	Black Raychem ATUM, MIL-I-23053

##### **Finish :**

Body, Ferrule	Nickel
Coupling Nut	Nickel
Center Contact	Gold

##### **Notes :**

1) Please refer to T-1901008 Termination Instruction sheet for strip dimensions & instructions.